

# COMPRESSION FITTINGS

## Specifications:


Lock nut: Black Polypropylene.  
 Body: Black Polypropylene.  
 Split Ring: White Acetal Resin.  
 'O' Ring: Nitrile Rubber  
 Max.working temp: 80 °C / 176°F.  
 Max.working pressure @ 20°C 10 Atm / 150 psi.

## MALE ADAPTOR



Catalogue No.	Dim. mm	BSP Male
70-26-01	16	½"
70-26-02	16	¾"
70-26-11	20	½"
70-26-12	20	¾"
70-26-13	20	1"
70-26-21	25	½"
70-26-22	25	¾"
70-26-23	25	1"
70-26-32	32	¾"
70-26-33	32	1"
70-26-34	32	1¼"
70-26-43	40	1"
70-26-44	40	1¼"
70-26-45	40	1½"
70-26-46	40	2"
70-26-53	50	1"
70-26-54	50	1¼"
70-26-55	50	1½"
70-26-56	50	2"
70-26-64	63	1¼"
70-26-65	63	1½"
70-26-66	63	2"
70-26-67	63	2½"
70-26-76	75	2"
70-26-77	75	2½"
70-26-78	75	3"
70-26-96	90	2"
70-26-97	90	2½"
70-26-98	90	3"
70-26-99	90	4"
70-26116	110	2"
70-26118	110	3"
70-26119	110	4"

## COUPLING



Catalogue No.	Diam. mm	Diam. mm
70-16-00	16	16
70-16-11	20	20
70-16-22	25	25
70-16-33	32	32
70-16-44	40	40
70-16-55	50	50
70-16-66	63	63
70-16-77	75	75
70-16-99	90	90
70-16111	110	110

## FEMALE ADAPTOR



Catalogue No.	Dim. mm	BSP Female
70-36-01	16	½"
70-36-02	16	¾"
70-36-11	20	½"
70-36-12	20	¾"
70-36-13	20	1"
70-36-22	25	¾"
70-36-23	25	1"
70-36-32	32	¾"
70-36-33	32	1"
70-36-34	32	1¼"
70-36-43	40	1"
70-36-44	40	1¼"
70-36-45	40	1½"
70-36-54	50	1¼"
70-36-55	50	1½"
70-36-56	50	2"
70-36-65	63	1½"
70-36-66	63	2"
70-36-76	75	2"
70-36-77	75	2½"
70-36-78	75	3"
70-36-96	90	2"
70-36-98	90	3"
70-36-99	90	4"
70-36118	110	3"
70-36119	110	4"

## REDUCING COUPLING



Catalogue No.	Diam. mm	Diam. mm
70-16-10	20	16
70-16-21	25	20
70-16-32	32	25
70-16-42	40	25
70-16-43	40	32
70-16-52	50	25
70-16-53	50	32
70-16-54	50	40
70-16-63	63	32
70-16-64	63	40
70-16-65	63	50
70-16-75	75	50
70-16-76	75	63
70-16-96	90	63
70-16-97	90	75
70-16119	110	90

## REPAIR COUPLING



Catalogue No.	Diam. mm	Diam. mm
70-05-44	40	40
70-05-55	50	50
70-05-66	63	63
70-05-77	75	75
70-05-99	90	90
70-05111	110	110

# COMPRESSION FITTINGS

**TEE**



Catalogue No.	Diam. mm	Diam. mm	Diam. mm
70-46-00	16	16	16
70-46-11	20	20	20
70-46-22	25	25	25
70-46-33	32	32	32
70-46-44	40	40	40
70-46-55	50	50	50
70-46-66	63	63	63
70-46-77	75	75	75
70-46-99	90	90	90
70-46111	110	110	110

**REDUCING TEE**



Catalogue No.	Diam. mm	Diam. mm	Diam. mm
70-48-10	20	16	20
70-48-21	25	20	25
70-48-32	32	25	32
70-48-43	40	32	40
70-48-54	50	40	50
70-48-65	63	50	63
70-48-76	75	63	75
70-48-97	90	75	90
70-48119	110	90	110

**FEMALE TEE**



Catalogue No.	Diam. mm	BSP Fem	Diam. mm
71-46-01	16	1/2"	16
71-46-02	16	3/4"	16
71-46-11	20	1/2"	20
71-46-12	20	3/4"	20
71-46-21	25	1/2"	25
71-46-22	25	3/4"	25
71-46-23	25	1"	25
71-46-32	32	3/4"	32
71-46-33	32	1"	32
71-46-34	32	1 1/4"	32
71-46-43	40	1"	40
71-46-44	40	1 1/4"	40
71-46-45	40	1 1/2"	40
71-46-46	40	2"	40
71-46-54	50	1 1/4"	50
71-46-55	50	1 1/2"	50
71-46-56	50	2"	50
71-46-65	63	1 1/2"	63
71-46-66	63	2"	63
71-46-76	75	2"	75
71-46-78	75	3"	75
71-46-98	90	3"	90
71-46119	110	4"	110

**MALE TEE**



Catalogue No.	Diam. mm	BSP male	Diam. mm
71-36-11	20	1/2"	20
71-36-22	25	3/4"	25
71-36-33	32	1"	32
71-36-44	40	1 1/4"	40
71-36-55	50	1 1/2"	50
71-36-66	63	2"	63

**FEMALE ELBOW**



Catalogue No.	Diam. mm	BSP Fem.
70-70-01	16	1/2"
70-70-11	20	1/2"
70-70-12	20	3/4"
70-70-21	25	1/2"
70-70-22	25	3/4"
70-70-23	25	1"
70-70-32	32	3/4"
70-70-33	32	1"
70-70-34	32	1 1/4"
70-70-43	40	1"
70-70-44	40	1 1/4"
70-70-45	40	1 1/2"
70-70-55	50	1 1/2"
70-70-56	50	2"
70-70-65	63	1 1/2"
70-70-66	63	2"
70-70-76	75	2"
70-70-77	75	2 1/2"
70-70-78	75	3"
70-70-98	90	3"

**MALE ELBOW**



Catalogue No.	Diam. mm	BSP male
70-66-01	16	1/2"
70-66-02	16	3/4"
70-66-11	20	1/2"
70-66-12	20	3/4"
70-66-21	25	1/2"
70-66-22	25	3/4"
70-66-23	25	1"
70-66-32	32	3/4"
70-66-33	32	1"
70-66-34	32	1 1/4"
70-66-43	40	1"
70-66-44	40	1 1/4"
70-66-45	40	1 1/2"
70-66-55	50	1 1/2"
70-66-56	50	2"
70-66-65	63	1 1/2"
70-66-66	63	2"
70-66-78	75	3"
70-66-98	90	3"
70-66119	110	4"

# COMPRESSION FITTINGS

## ELBOW



Catalogue No.	Diam. mm	Diam. mm
70-56-00	16	16
70-56-11	20	20
70-56-22	25	25
70-56-33	32	32
70-56-44	40	40
70-56-55	50	50
70-56-66	63	63
70-56-77	75	75
70-56-99	90	90
70-56111	110	110

## CAP



Catalogue No.	Diam. mm
71-26-20	25
71-26-30	32
71-26-40	40
71-26-50	50
71-26-60	63
71-26-70	75
71-26-90	90
71-26110	110

## FLANGE ADAPTOR



Catalogue No.	Diam. mm	Diam. PN40
71-56-55	50	1½"
71-56-66	63	2"
71-56-77	75	2½"
71-56-98	90	3"
71-56119	110	4"

## MALE ADAPTOR WITH BRASS THREADED INSERT

Catalogue No.	Diam.	BSP male
71-28-11	20	½"
71-28-22	25	¾"
71-28-33	32	1"
71-28-44	40	1¼"
71-28-55	50	1½"
71-28-66	63	2"

## UNIVERSAL TRANSITION COUPLING

Catalogue No.	Diam. mm	BSP mm
70-98-22	15/22	25
70-98-24	20/27	25
70-98-34	20/27	32
70-98-26	27/34	25
70-98-36	27/34	32

## BLACK POLYETHYLENE PIPE



Bar Rating : 4/6/8/10/12

Sizes: from 32mm

Price on application

## BLUE M.D.P.E. PIPE



Bar Rated 12.5

Sizes : from 32mm

Price on application