




CAST IRON SWING CHECK VALVE – PN16					
	Description	Size	Weight kilos	Length mm	£
	Flanged PN16Body, Body Seats, Cast Iron, Swing Seat Ring Rubber EPDM. Pressure/Temp in accordance EN1092-2:197.	1 ½"	9	180	63.00
		2"	11	200	75.00
		2 ½"	15.2	240	104.00
		3"	20.5	260	130.00
		4"	31.5	300	174.00
		5"	46	350	249.00
		6"	60	400	315.00
		8"	120	500	770.00
		10"	180	600	1252.00
12"		250	700	1700.00	

WRAS					
CAST IRON SWING CHECK VALVE					
	Description	Size	Weight Kilos	Length mm	£
	Flanged PN16, GG25 Body, Blue epoxy coated Body seats bronze, Water works use, Temperature Range: -10°C + 70°C (DIN2401-2)	2"	13	203	162.00
		3"	22	241	191.00
		4"	26	292	239.00
		6"	75	356	393.00
		8"	134	495	1031.00
		10"	163	622	1229.00
		12"	223	698	1706.00

CAST IRON ‘Y’ – TYPE STRAINER – PN16					
	Description	Size	Weight Kilos	Length mm	£
	Flanged PN16 body Stainless steel filter mesh screen with drain plug. Pressure/Temp in accordance with : EN1092-2:1997	½"	3	130	27.00
		¾"	4	150	29.00
		1"	5	160	35.00
		1 ¼"	7	180	38.00
		1 ½"	8	200	49.00
		2"	11	230	50.00
		2 ½"	16	290	74.00
		3"	18	310	89.00
		4"	27	350	134.00
		5"	35	400	202.00
		6"	47	480	295.00
		8"	85	600	568.00
		10"	145	730	1096.00
12"		200	850	1774.00	

Visit our website @ www.maddisonwatertech.co.uk