




		<b>CAST IRON GATE VALVE</b>			
	Description	Size	Weight Kilos	Length mm	£
	Conforms to DIN3202 F4 standard, Cast Iron Body, Cast Brass Seat, Stainless Steel Stem, Inside Screw, Non Rising Stem to fit flanges PN16. Maximum working pressure 16 bar.	1 ½"	10.4	140	61.00
		2"	11.0	150	98.00
		2 ½"	12.8	170	120.00
		3"	16.7	180	130.00
		4"	23.5	190	208.00
		5"	36	200	238.00
		6"	43	210	293.00
		8"	63	230	400.00
		10"	97	250	657.00
12"		132	270	829.00	

		<b>DUCTILE IRON GATE VALVE - WRAS Approved Product</b>			
	Description	Size	Weight kilos	Length mm	£
	Flanged to PN10/PN16 – CAP TOP ( Hand wheel available) Ductile iron GGG40, Epoxy coated blue, EPDM covered resilient seal. Clock wise closing ( Anti-clockwise on request)	2"	10	178	128.00
		2 ½"	12.5	190	152.00
		3"	17	203	179.00
		4"	21	229	193.00
		6"	38	267	266.00
		8"	58	292	557.00
		10"	86	330	856.00
		12"	121	356	1109.00

		<b>HAND WHEEL TO SUIT DUCTILE IRON GATE</b>				
	Description	Size	Weight kilos	Length mm	£	Carriage
	Hand wheel for service connection , valves and gate valves designed according to DIN/EN	2"	0.30	150	18.50	12.50
		2 ½"	0.51	175	18.50	12.50
		3"	0.51	175	18.50	12.50
		4"	0.72	200	18.50	12.50
		6"	1.62	300	18.50	12.50
		8"	1.88	350	29.50	12.50
		10"	2.25	400	29.50	12.50
		12"	2.40	500	29.50	12.50

Visit our website @ [www.maddisonwatertech.co.uk](http://www.maddisonwatertech.co.uk)