




# THREADED VALVES

	<b>BRASS GATE VALVE</b>			
	Description	Size	Weight Kilos	Length mm
 <p>To BS5154, PN20, screwed BSPT female. Cast hand wheel Temperature range : 20°C + 120°C</p>	¼"	0.18	35	4.90
	½"	0.18	36	6.15
	¾"	0.32	45	8.40
	1"	0.42	51	11.20
	1 ¼"	0.66	55	16.75
	1 ½"	0.86	58	21.75
	2"	1.28	64	30.85
	2 ½"	2.50	77	57.00
	3"	3.50	85	75.00
	4"	5.5	100	123.00

	<b>BRASS BALL VALVE – STANDARD PATTERN – RED LEVER</b>			
	Description	Size	Weight Kilos	Length mm
 <p>Nickel plates brass body Screwed BSP PTFE seats, PTFE Stem seal Anti blow out stem Red PVC coated steel lever Temp 0° C - 90° C Pressure ¼" – 1" PN32 1 ¼" – 2" PN25</p>	¼"	0.18	35	5.75
	½"	0.18	36	5.75
	¾"	0.32	45	8.50
	1"	0.42	51	12.00
	1 ¼"	0.66	55	20.00
	1 ½"	0.86	58	28.00
	2"	1.28	64	42.00
	2 ½"	2.50	77	95.000
	3"	3.50	85	108.00
	4"	5.5	100	165.00

	<b>BRASS NON RETURN VALVE</b>			
	Description	Size	Weight Kilos	Length mm
 <p>To BS5154, PN20, screwed BSPT female. Cast hand wheel Temperature range : 20°C + 120°C</p>	3/8"	0.17	47	6.00
	½"	0.15	47	5.00
	¾"	0.21	54	7.00
	1"	0.33	64	11.00
	1 ¼"	0.50	76	15.00
	1 ½"	0.66	83	19.00
	2"	1.00	98	28.00
	2 ½"	1.57	116	42.00
	3"	2.26	135	65.00
	4"	3.78	164	114.00

Visit our website @ [www.maddisonwatertech.co.uk](http://www.maddisonwatertech.co.uk)