




WAFER PATTERN BUTTERFLY VALVE – EPDM LINER				
Description	Size	Weight Kilos	Length mm	£
 <p>Epoxy painted cast iron body. Lever operated. Nickel plated ductile iron disc. ISO5211 Top. Max pressure 16 bar to fit flanges PN10/16. Temperature range 10°C + 120°C</p>	2"	3.80	42	52.00
	2 ½"	4.40	44.7	55.00
	3"	5	45.2	60.00
	4"	7	52.1	76.00
	5"	8	54.4	93.00
	6"	8	54.4	118.00
	8"	16.2	55.8	161.00
	10"	24.8	65.7	248.00
	12"	37	76.5	346.00

CARBON STEEL WAFER CHECK VALVE				
Description	Size	Weight Kilos	Length mm	£
 <p>Stainless Steel Flap NBR O-Ring flap seat To suit PN10/16 flanges. No O Ring in face.</p>	2"	0.90	14	64.00
	2 ½"	1.20	14	69.00
	3"	1.50	14	81.00
	4"	2.40	18	96.00
	5"	3.40	18	114.00
	6"	4.20	18	140.00
	8"	7.50	22	222.00

DUAL PLATE CHECK VALVE				
Description	Size	Weight Kilos	Length mm	£
 <p>Epoxy coated cast iron body. EPDM seat, Stainless steel 304 plates. Pins and springs. To fit flanges PN16 Maximum working pressure 16 bar.</p>	2"	1.40	43	52.00
	2 ½"	2.08	46	59.00
	3"	3.46	64	69.00
	4"	4.50	64	84.00
	5"	6.20	70	111.00
	6"	8.80	76	135.00
	8"	15.2	89	215.00
	10"	26.24	114	362.00
12"	29.30	114	463.00	

Visit our website @ www.maddisonwatertech.co.uk